



QG Nylon 66 Cable Ties

Low Smoke, Zero Halogen
Flame Retardant to UL94-V2
UV Resistant

-40 to +85°C
Standard Colour Black
Other colour available on request

Item No.	Length mm	Width mm	Max. Bundle Dia. mm	Min. Tensile Strength kg
GT-80M	80	2.5	15	8
GT-100M	100	2.5	22	8
GT-120M	120	2.5	30	8
GT-150M	150	2.5	35	8
GT-200M	200	2.5	50	8
GT-150I	150	3.6	35	18
GT-200I	200	3.6	50	18
GT-250I	250	3.6	65	18
GT-300I	300	3.6	80	18
GT-370I	370	3.6	102	18
GT-150ST	150	4.8	35	22
GT-200ST	200	4.8	50	22
GT-250ST	250	4.8	65	22
GT-300ST	300	4.8	82	22
GT-370ST	370	4.8	102	22
GT-430ST	430	4.8	110	22
GTE-200HD	200	7.6	50	55
GTE-250HD	250	7.6	63	55
GTE-300HD	300	7.6	82	55
GTE-370HD	370	7.6	90	55
GTE-430HD	430	7.6	118	55
GTE-530HD	530	7.6	150	55
GT-430HD	430	9	125	80
GT-530HD	530	9	150	80
GT-710HD	710	9	205	80
GT-780HD	776	9	245	80
GT-820HD	815	9	265	80
GT-1020HD	1020	9	285	80





QG Self-Adhesive Cable Tie Bases

Low Smoke, Zero Halogen
Flame Retardant to UL94-V2
Quick assembly in clean applications
Stabilise and secure wiring bundles

Nylon 66 Natural
Allows 4-way entry for cable ties
Mounting holes for alternative fixing

Item No.	Length mm	Width mm	Max. Tie Width mm	Mounting Hole Dia. mm	Bag QTY
ABM-20	20	20	5	3.5	100
ABM-25	25	25	5	4.5	100
ABM-30	30	30	5	6.5	100



Changzhou Qiaoguang Electrical Appliance Co., Ltd

Tel: 86-519-8697 2201

Fax: 86-519-8697 2990

Address: No. 223, West Hehai Road, Changzhou, Jiangsu, PRC